

INSTECH Drying Cabinet Conforms to the latest world standards

Product Features

- /~ Suitable For Drying of CSSD Materials
- /~ Sturdy Construction for Long Service
- /~ Air Circulation Interlocked with Heating
- /~ High Grade Insulation
- /~ Digital Temperature & Timer Controller
- /~ Safety Against Over Heating
- /~ MOC SS-304 (SS-316 Optional)
- /~ Entails Best In class Mechanised Finishing
- /~ Smooth surfaces and rounded corners for easy cleaning
- /~ Interlocking system and sensors for safety and monitoring
- /~ Range: Temp Ambient- 110°C (with PT-100 Sensor)
- /~ Time upto 99 minutes
- /~ Power : 230V Single Phase AC
- /~ Ready to use on connected



IS-DC-200

Bespoke Customized Capabilities

- Option 1 - HEPA Filter for Ultra clean Air.
- Option 2 - Real time Data Acquisition.
- Option 3 - Double Door with Interlocking.
- Option 4 - Silicon Rubber Suspension Grips.
- Option 5 - Colored LED Touch Screen.



IS-DC-270

SNo.	Model No.	Capacity	Dimensions (mm)	Power Consumption
1.	IS-DC-150	150 Ltr.	620 X 400 X 610.	1.9 KW
2.	IS-DC-200	200 Ltr.	620 X 400 X 810.	2.4 KW
3.	IS-DC-270	270 Ltr.	620 X 400 X 1100.	3.4 KW
4.	IS-DC-525	525 Ltr.	700 X 700 X 1100.	8 KW